

TREMPROOF 201/60 - SLVersion 5.0
REVISION DATE: 04/16/2014

Print Date 04/17/2014

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : **TREMPROOF 201/60 - SL**

Product code : 859506 805

COMPANY : Tremco Incorporated
3735 Green Road
Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST
Emergency Phone : (216) 765-6727 8:30 - 5:00 EST
After Hours: Chemtrec 1-800-424-9300

Product use : Coating

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Black. Liquid. May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization.

Eyes : Vapor and/or mist may cause eye irritation.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause sensitization resulting in irritation, itching and redness.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. Prolonged inhalation or ingestion of large amounts of 1-chloro-4-(trifluoromethyl)-benzene may cause liver and kidney damage based on laboratory animal studies. Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). Carbon black is encapsulated by resin and not expected to have adverse effects unless made airborne. A long-term NTP study showed that oral exposure to toluene diisocyanate (TDI) caused cancer in rats and mice. A lifetime inhalation study sponsored by the International Isocyanate Institute did not show carcinogenic activity in rats. May cause allergic skin and respiratory sensitization. Fillers are encapsulated and not expected to be released from product under normal conditions of use. Prolonged or repeated exposure to mineral spirits (petroleum naphtha or stoddard solvent) may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, and adverse liver, kidney, and lung effects.

Target Organs: Eye, Lung, Liver, Kidney, Skin, Nerve

TREMPROOF 201/60 - SL

 Version 5.0
 REVISION DATE: 04/16/2014

Print Date 04/17/2014

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Aromatic process oil	64741-62-4	15.0 - 40.0
Calcium Carbonate (Limestone)	1317-65-3	15.0 - 40.0
Polyurethane Polymer	NJ TSRN# 51721300-5024P	15.0 - 40.0
P-chlorobenzotrifluoride	98-56-6	7.0 - 13.0
Calcium oxide	1305-78-8	3.0 - 7.0
Stoddard solvent (Mineral Spirits)	8052-41-3	3.0 - 7.0
Carbon Black	1333-86-4	1.0 - 5.0
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1.0
1,2,4-Trimethylbenzene	95-63-6	0.1 - 1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
Skin contact	:	Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point	:	150 °F, 66 °C
Method	:	Setaflash Closed Cup
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Carbon monoxide and carbon dioxide can form. Smoke, fumes. Hydrocyanic acid and nitrogen oxides can form.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	Product may ignite if heated in excess of its flash point. Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors. Vapors may travel to sources of ignition and flashback.

TREMPROOF 201/60 - SLVersion 5.0
REVISION DATE: 04/16/2014

Print Date 04/17/2014

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Change soiled work clothes frequently. Clean hands thoroughly after handling. Do not smoke, weld, generate sparks, or use flame near container. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Store under dry warehouse conditions away from heat and all ignition sources.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**Personal protection equipment**

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Select positive pressure supplied air respirator (TC19C or equivalent) for isocyanates.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Calcium oxide	1305-78-8	ACGIH TWA:	2 mg/m3	
		OSHA PEL:	5 mg/m3	
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.

TREMPROOF 201/60 - SL

Version 5.0

Print Date 04/17/2014

REVISION DATE: 04/16/2014

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Stoddard solvent (Mineral Spirits)	8052-41-3	ACGIH TWA: OSHA PEL:	100 ppm 2,900 mg/m3	
Carbon Black	1333-86-4	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	3.5 mg/m3 3.5 mg/m3 15 mg/m3 5 mg/m3	Total dust. Respirable fraction.
Hydrotreated heavy naphthenic distillate	64742-52-5	OSHA PEL: OSHA PEL: ACGIH TWA:	2,000 mg/m3 5 mg/m3 5 mg/m3	Mist. Inhalable fraction.
1,2,4-Trimethylbenzene	95-63-6	ACGIH TWA:	25 ppm	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquid
Color	: Black
Odor	: Solvent
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: Not available.
Water solubility	: Negligible
Specific Gravity	: 1.35
% Volatile Weight	: 15 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Strong acids.Strong bases.Amines.Water or moisture.Alcohols.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No Data Available



TREMPROOF 201/60 - SL

Version 5.0
REVISION DATE: 04/16/2014

Print Date 04/17/2014

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

This product or its components are listed on, or exempt from the Canadian Domestic Substances List. All components are listed or exempt from the TSCA inventory. This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard
Fire Hazard

OSHA Hazardous Components :

Aromatic process oil	64741-62-4
Calcium Carbonate (Limestone)	1317-65-3
Calcium oxide	1305-78-8
Stoddard solvent (Mineral Spirits)	8052-41-3
Carbon Black	1333-86-4
Hydrotreated heavy naphthenic distillate	64742-52-5

TREMPROOF 201/60 - SL

Version 5.0
 REVISION DATE: 04/16/2014

Print Date 04/17/2014

1,2,4-Trimethylbenzene 95-63-6

OSHA Status: Considered : Irritant
 hazardous based on the : Sensitizer
 following criteria: : Carcinogen

OSHA Flammability : IIIA

Regulatory VOC (less water and : 95 g/l
 exempt solvent)

VOC Method 310 : 6.36 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Carbon Black 1333-86-4
 Hydrotreated heavy naphthenic distillate 64742-52-5

U.S. State Regulations:

MASS RTK Components : Calcium Carbonate (Limestone) 1317-65-3
 Calcium oxide 1305-78-8
 Stoddard solvent (Mineral Spirits) 8052-41-3
 Carbon Black 1333-86-4

Penn RTK Components : Aromatic process oil 64741-62-4
 Calcium Carbonate (Limestone) 1317-65-3
 Polyurethane Polymer NJ TSRN# 51721300-5024P
 P-chlorobenzotrifluoride 98-56-6
 Calcium oxide 1305-78-8
 Stoddard solvent (Mineral Spirits) 8052-41-3
 Carbon Black 1333-86-4

NJ RTK Components : Aromatic process oil 64741-62-4
 Calcium Carbonate (Limestone) 1317-65-3
 Polyurethane Polymer NJ TSRN# 51721300-5024P
 P-chlorobenzotrifluoride 98-56-6
 Calcium oxide 1305-78-8
 Stoddard solvent (Mineral Spirits) 8052-41-3
 Carbon Black 1333-86-4
 Hydrotreated heavy naphthenic distillate 64742-52-5

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	2
Flammability	2
Reactivity	1
PPE	

0 = Minimum
 1 = Slight
 2 = Moderate
 3 = Serious
 4 = Severe

TREMPROOF 201/60 - SL

Version 5.0
REVISION DATE: 04/16/2014

Print Date 04/17/2014

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
DOT - Department of Transportation
DSL - Domestic Substance List
EPA - Environmental Protection Agency
HMIS - Hazardous Materials Information System
IARC - International Agency for Research on Cancer
MSHA - Mine Safety Health Administration
NDSL - Non-Domestic Substance List
NIOSH - National Institute for Occupational Safety and Health
NTP - National Toxicology Program
OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit
RCRA - Resource Conservation and Recovery Act
RTK - Right To Know
SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit
TLV - Threshold Limit Value
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
V - Volume
VOC - Volatile Organic Compound
WHMIS - Workplace Hazardous Materials Information System

